



Standard Installation

Specifications

| Model | Voltage (V) | Speed | Frequency (Hz) | Power consumption (W) | Airflow(m ³ /h) | | Sound (db) | Weight (kg) |
|------------|-------------|-------|----------------|-----------------------|----------------------------|---|------------|-------------|
| | | | | | 0Pa | - | | |
| FR-LW2490V | 220 | Boost | 50 | 159 | 1200 | - | 52 | 26 |
| | | F3 | | 93 | 1035 | - | 48 | |
| | | F2 | | 72 | 870 | - | 45 | |
| | | F1 | | 50 | 740 | - | 40 | |
| | 230 | Boost | | 160 | 1200 | - | 52 | |
| | | F3 | | 95 | 1040 | - | 48 | |
| | | F2 | | 74 | 865 | - | 45 | |
| | | F1 | | 51 | 740 | - | 41 | |
| | 240 | Boost | | 161 | 1200 | - | 52 | |
| | | F3 | | 96 | 1040 | - | 48 | |
| | | F2 | | 75 | 870 | - | 45 | |
| | | F1 | | 52 | 740 | - | 41 | |

| | | | | | | | |
|-------------|------------------|-----------------------|------------------------|----------------------|-----------------|------------------|---|
| Motor class | 10 Pole DC motor | insulation resistance | Over 10MΩ (500Vmegger) | Withstanding voltage | AC1000V for1min | Insulation class | E |
|-------------|------------------|-----------------------|------------------------|----------------------|-----------------|------------------|---|

Airflow measured by JIS C9603 chamber method

| Mark | Revised record | Date |
|------|----------------|------|
| △ | | |

| | | | |
|-----------------|--------------|-------------------------|-------------|
| FR-LW2490V GR | | Gray | |
| FR-LW2490V BK | | Black | |
| Model | Product code | Color | Note |
| Created date | 21/05/2024 | Product category | Cooker Hood |
| Updated date | | Model | FR-LW2490V |
| -FUJIOH- | Scale 1/10 | Product outline drawing | |